

## 1993 4T60-E ID Chart

Model Code	Description	Differential Ratio	Sprocket Ratio	Overall Ratio	VSS Reluctor	Stall Speed
3ABW	4.9L Cadillac C Body	3.06	37/33	2.73	30	1825
3AMW	4.9L Cadillac E/K Body	3.33	37/33	2.97	31	1825
3ANW	4.9L Cadillac C Body	3.33	37/33	2.97	30	1825
3APW	4.9L Cadillac E/K Body (export)	3.33	37/33	2.97	31	1825
3AVW	4.9L Cadillac C Body	3.06	37/33	2.73	30	1825
3AWW	4.9L Cadillac C Body (export)	3.33	37/33	2.97	30	1825
3AZW	4.9L Cadillac C Body (limo)	3.06	37/33	2.73	32	1825
3BTW	3800 C Body	3.33	37/33	2.97	31	1897
3BYW	3800 H Body	3.06	35/35	3.06	31	1897
3CLW	3800 C/H Body	2.84	35/35	2.84	30	1420
3CSW	3800 C/H Body (export)	3.33	35/35	3.33	30	1897
3CTW	3800 H Body SSE	3.06	35/35	3.06	31	1897
3CXW	3800 C Body	3.06	37/33	2.73	31	1897
3CZW	3800 H Body SSE/SSEi	3.33	37/33	2.97	31	1897
3PHW	3800 H Body SSE	3.33	37/33	2.97	31	1897
3WAW	3800 C/H Body & GM200 (U-body)	3.06	35/35	3.06	31	1897
3YMW	3800 C/H Body	2.84	35/35	2.84	30	1420
3YZW	3800 C/H Body (export)	3.06	35/35	3.06	30	1897
3CWW	3.4L W Body (non-PWM TCC)	3.06	33/37	3.43	30	2095
3CMW	3.1L W Body (non-PWM TCC)	3.33	35/35	3.33	30	2060
3YLW	3800 H Body	2.84	35/35	2.84	31	1420
3YRW	3800 E Body	3.06	35/35	3.06	30	1897
3BHW	3.1L W Body (structural side cover 4-bolt)	3.33	35/35	3.33	30	2095