

1994 4T60-E ID Chart

Model Code	Description	Differential Ratio	Sprocket Ratio	Overall Ratio	VSS Reluctor	Stall Speed
4ATW	4.9L Cadillac K Body	3.06	37/33	2.73	31	1825
4CLW	2.3L Quad4 N Body (6-bolt side cover)	3.06	33/37	3.43	29	2095
4PHW	2.3L Quad4 N Body (6-bolt side cover)	3.33	33/37	3.73	29	2363
4AFW	3.1L W Body (4-bolt side cover)	3.33	35/35	3.33	30	2095
4AJW	3.1L A Body (export)	3.33	37/33	2.97	29	1630
4CMW	3.1L W Body (non-PWM TCC)	3.33	35/35	3.33	30	2060
4PAW	3.1L A Body	3.33	37/33	2.97	29	1630
4WSW	3.1L L/N Body (6-bolt side cover)	3.33	37/33	2.97	29	1630
4PBW	3.4L W Body (4-bolt side cover)	3.06	33/37	3.43	30	2060
4BLW	3800 W Body (4-bolt side cover)	3.06	35/35	3.06	31	1897
4KUW	3800 U Body	3.06	35/35	3.06	31	1897
4KHW	3800 Supercharged H Body	3.33	37/33	2.97	31	1897
4PFW	3800 H Body	3.06	35/35	3.06	31	1897
4WAW	3800 C/H Body	3.06	35/35	3.06	31	1897
4YCW	3800 Supercharged C/H Body	3.33	37/33	2.97	31	1897
4YMW	3800 H Body	2.84	35/35	2.84	30	1420
4YZW	3800 H Body	3.06	35/35	3.06	30	1897